



US012747040B1

(12) **United States Patent**
Wuerl et al.

(10) **Patent No.:** **US 12,747,040 B1**
(45) **Date of Patent:** **Sep. 29, 2026**

(54) **REUSABLE SEPARATION SYSTEM FOR
ROCKET FAIRING AND PAYLOAD**

(71) Applicant: **Blue Origin Manufacturing, LLC**,
Huntsville, AL (US)

(72) Inventors: **Adam M. Wuerl**, Seattle, WA (US);
Joseph Paul Atkinson, Melbourne, FL
(US); **Todd James Buchholz**, Sun
Prairie, WI (US); **David Alan**
Degenhardt, Seattle, WA (US)

(73) Assignee: **Blue Origin Manufacturing, LLC**,
Huntsville, AL (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **19/091,753**

(22) Filed: **Mar. 26, 2025**

(51) **Int. Cl.**

B64G 1/64 (2006.01)

B64G 1/58 (2006.01)

B64G 1/62 (2006.01)

(52) **U.S. Cl.**

CPC **B64G 1/6457** (2023.08); **B64G 1/58**
(2013.01); **B64G 1/62** (2013.01); **B64G 1/641**
(2013.01)

(58) **Field of Classification Search**

CPC B64G 1/64; B64G 1/641; B64G 1/644;
B64G 1/645; B64G 1/6457

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,352,192 A * 11/1967 Webb F42B 15/36
102/378

4,896,847 A 1/1990 Gertsch

5,115,708 A * 5/1992 Spariat B64G 1/641
102/378

5,248,233 A * 9/1993 Webster F16B 5/0208
102/377

5,312,152 A * 5/1994 Woebkenberg, Jr. .. B64G 1/641
60/528

5,653,549 A 8/1997 Geyer et al.

5,829,253 A * 11/1998 Long B64G 1/64
60/528

(Continued)

FOREIGN PATENT DOCUMENTS

CN 109229433 B 4/2020

CN 114194422 A 3/2022

(Continued)

OTHER PUBLICATIONS

Drescher, Oliver, "Cork Based Thermal Protection System for
Sounding Rocket Applications—Development and Flight Testing",
23rd ESA PAC Symposium 2017, Jun. 1, 2017, 9 pages.

(Continued)

Primary Examiner — Joshua J Michener

Assistant Examiner — Cindi M Curry


(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson
& Bear, LLP

(57)

ABSTRACT

A separation system for a rocket having a payload release
assembly and a fairing release assembly. Release devices
secure and then separate the payload and fairing from the
rocket. The release devices have rotatable bolts that retract.
The release devices are cooled to survive reentry and may
then be reused. A heat shield at the forward end of the rocket
allows for reuse of the rocket and separation system. The
rocket may be a reusable, upper (e.g. second) stage rocket.

20 Claims, 16 Drawing Sheets



(56)

References Cited**U.S. PATENT DOCUMENTS**

6,126,115 A * 10/2000 Carrier B64G 1/641
294/82.26

6,758,142 B1 7/2004 Seaquist

6,789,767 B2 9/2004 Mueller et al.

10,072,915 B2 9/2018 Medina et al.

10,934,029 B2 3/2021 Bower et al.

12,366,218 B2 * 7/2025 Horn F02K 9/42

2003/0141416 A1 7/2003 Telford

2006/0097113 A1 * 5/2006 Landsberg B64G 1/6457
244/137.4

2009/0127399 A1 5/2009 Mueller et al.

2015/0050078 A1 2/2015 Laughlin

2021/0094707 A1 4/2021 Houghton et al.

2022/0194635 A1 6/2022 Aston et al.

2022/0194636 A1 6/2022 Freestone et al.

2024/0083601 A1 * 3/2024 Johnson B64G 1/643

2024/0132234 A1 * 4/2024 Cespedosa Castán B64G 1/641

FOREIGN PATENT DOCUMENTS

CN 112340069 B 10/2022

CN 116119041 A 5/2023

DE 1506134 A1 4/1970

EP 2161199 A1 3/2010

FR 2693978 A1 1/1994

JP H08219134 A 8/1996

OTHER PUBLICATIONS

Finkbeiner, Joshua R. et al., "Apollo Seals: A Basis for the Crew Exploration Vehicle Seals", Nov. 2006, 31 pages.

Pan, Xueting et al., "Reusable SMA Actuated Non-explosive Lock-release Mechanism for Space Application", International Journal of Smart and Nano Materials 11(1): 65-77, Jan. 6, 2020, 14 pages. URL: <https://doi.org/10.1080/19475411.2019.1711462>.

"PSR 1575 mm", SatCatalog, Oct. 11, 2022, 4 pages. URL: <https://www.satcatalog.com/component/psr-1575-mm/>.

Rogers, William F. et al., "Pyrotechnic Shock at the Orbiter/External Tank Forward Attachment", The 11th Space Simulation Conf., 33-42, Jan. 1, 1980, 10 pages.

"Space Shuttle Program Payload Bay Payload User's Guide", National Aeronautics and Space Administration, Dec. 2000, 255 pages.

"SpaceX—Starship Users Guide", Space Exploration Technologies Corp., Mar. 2020, 6 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2B




FIG. 2C




FIG. 2D

FIG. 2E




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G




FIG. 3H

FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B

1

REUSABLE SEPARATION SYSTEM FOR ROCKET FAIRING AND PAYLOAD

BACKGROUND

Field

The technology relates generally to separation systems for a rocket, and more specifically a reusable fairing and payload separation system for reusable second stage rockets.

Description of the Related Art

Launch vehicles transport payloads such as spacecraft into orbit or to other planetary bodies. The vehicle may include multiple stages, such as a first stage rocket for initial launch and a second stage rocket for delivering the payload to the final destination. Traditional stages for launch vehicles cannot survive the environment upon reentry to earth's atmosphere. Thus any systems for supporting and separating a component, such as a payload or the fairing, from the vehicle are typically expendable and thus non-reusable. Such systems are therefore not intended to withstand reentry through the atmosphere. Even for reusable rockets, such as reusable first or second stages, typical separation systems are jettisoned or otherwise non-reusable, for example due to damage upon reentry. Therefore, there exists a need for improvements to these and other drawbacks of traditional rocket separation systems.

SUMMARY

Each embodiment disclosed herein has several aspects, no single one of which is solely responsible for the disclosure's desirable attributes. Without limiting the scope of this disclosure, its more prominent features will now be briefly discussed. After considering this discussion, and particularly after reading the section entitled "Detailed Description," one will understand how the features of the embodiments described herein provide advantages over existing approaches to rocket separation systems for fairings and payloads.

In some aspects, a release device for a separation system of a rocket includes a tubular body extending along a longitudinal axis from a proximal end to a distal end and defining a channel extending axially therethrough; and a bolt including an axially extending shaft configured to be positioned within the channel of the tubular body and a transversely elongated head on a distal end of the shaft, wherein the bolt is configured to rotate about the longitudinal axis from a first position where the head is configured to engage an expendable component and a second position where the head is configured to disengage from the expendable component to thereby allow the bolt to translate proximally through the channel and allow the expendable component to separate from the rocket.

In some aspects, the release device further includes a transverse actuation arm configured to rotate the shaft.

In some aspects, the release device further includes a biasing element configured to bias the bolt proximally.

In some aspects, the head is configured to engage a seat of the expendable component, the seat defining a transversely elongated slot.

In some aspects, a proximal surface of the head is helical.

In some aspects, the release device includes cooling channels extending through the body and the bolt configured to flow coolant therethrough.

2

In some aspects, the cooling channel extending through the bolt extends to a distal opening at a distal end of the bolt.

In some aspects, the expendable component includes an adaptor or a load spreader.

5 In some aspects, a release device for an expendable component of a rocket includes a body including a channel extending through the body from a proximal end to a distal end; a bolt including a shaft and a head on a distal end of the shaft; and a cooling system configured to flow coolant to the body and the bolt during reentry of the rocket into the atmosphere so that the release device is reusable.

In some aspects, the bolt is configured to heat up to cause the coolant to boil to prevent a temperature of the bolt from raising above a melting or annealing temperature of the bolt.

15 In some aspects, the cooling system includes a recess in the head of the bolt, wherein the recess is configured to hold the coolant that boils to cool the head of the bolt during reentry of the rocket through an atmosphere.

In some aspects, the bolt includes a cap coupled to a distal surface of the bolt, wherein the cap includes a plurality of channels, and wherein the coolant is configured to boil in the plurality of channels to vent vapor out of the recess in the head and to a surrounding atmosphere.

25 In some aspects, the cap includes a material with a high thermal diffusivity.

In some aspects, the bolt includes titanium and/or the body includes aluminum.

In some aspects, the body includes an end cap, and the cooling system includes an annular channel in the end cap.

30 In some aspects, a method of operating a release device with a component for securement with a rocket includes positioning the component at a distal end of the release device; distally translating a bolt of the release device into a recess of the component; and rotating the bolt from a second position to a first position to engage a head of the bolt with the component.

In some aspects, the method further includes rotationally biasing the bolt towards the first position.

40 In some aspects, the method further includes proximally biasing the bolt.

In some aspects, the method further includes rotating the bolt from the first position to the second position to disengage the bolt from the component and proximally translating the bolt out of the recess of the component to retract the bolt into a body of the release device.

45 In some aspects, the method further includes cooling the bolt during reentry of the rocket through an atmosphere.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other features of the present disclosure will become more fully apparent from the following description and appended claims, taken in conjunction with the accompanying drawings. Understanding that these drawings depict only several embodiments in accordance with the disclosure and are not to be considered limiting of its scope, the disclosure will be described with additional specificity and detail through use of the accompanying drawings.

50 In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made without departing from the spirit or scope of the subject matter presented here. It will be readily understood

3

that the aspects of the present disclosure, as generally described herein, and illustrated in the drawings, may be arranged, substituted, combined, and designed in a wide variety of different configurations, all of which are explicitly contemplated and make part of this disclosure.

FIG. 1A is a side view of an example rocket, shown as a second stage rocket, with an example separation system having a payload release assembly, a fairing release assembly, and a heat shield.

FIG. 1B is a side view of the second stage of FIG. 1A shown with an example payload supported by the payload release assembly and an example fairing (shown transparently) supported by a fairing release assembly.

FIG. 2A is a side perspective view of an embodiment of the separation system of FIG. 1A without the heat shield.

FIG. 2B is a side perspective view of the separation system of FIG. 2A and including the heat shield.

FIG. 2C is a side view of a schematic of an embodiment of payload and fairing release systems that may be used with the separation system of FIG. 2A.

FIG. 2D is a side view of a schematic of a portion of the separation system of FIG. 2B, including a release device, a standoff, a seal, and part of the heat shield.

FIG. 2E is a close-up side view of the schematic of the separation system of FIG. 1B supporting an example payload and an example fairing (shown transparently).

FIG. 3A is a cross-sectional view of an example embodiment of a release device that may be used with the release assemblies of the separation system of FIGS. 1A-2E.

FIG. 3B is a cross-sectional view of an example embodiment of a release device that may be used with the release assemblies of the separation system of FIGS. 1A-2E showing a bolt in an extended position.

FIG. 3C is a cross-sectional view of the release device of FIG. 3B showing the bolt in a retracted position.

FIGS. 3D-3G are top perspective views of the release device of FIG. 3A sequentially illustrating the bolt rotating from a first position to a second position and translating from the extended position to the retracted position.

FIG. 3H is a side view of an example embodiment of a bolt that can be used with the release devices of FIGS. 3A-3G.

FIG. 4A is a cross-sectional view of an example embodiment of a cooling system for a release device that may be used with the release devices of FIGS. 3A-3H.

FIG. 4B is a cross-sectional view of an upper portion of an example embodiment of a cooling system for a bolt that can be used with any of the release devices of FIGS. 3A-4A.

FIG. 5A is a schematic of an example embodiment of a cooling system architecture that can be used for any of the release devices of FIGS. 3A-4B, including a first flow path for providing coolant to the release devices, a second flow path for cooling coolant in the first flow path, and a head exchanger between the first flow path and the second flow path.

FIG. 5B is a schematic of another example embodiment of a cooling system architecture that can be used for any of the release devices of FIGS. 3A-4B, including a flow path for providing coolant to the release devices to passively cool the release devices.

DETAILED DESCRIPTION

The following detailed description is directed to certain specific embodiments for devices, systems, and methods related to a reusable payload interface for a reusable second stage of a multi-stage launch vehicle. In this description,

4

reference is made to the drawings wherein like parts or steps may be designated with like numerals throughout for clarity. Reference in this specification to “one embodiment,” “an embodiment,” or “in some embodiments” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present disclosure. The appearances of the phrases “one embodiment,” “an embodiment,” or “in some embodiments” in various places in the specification are not necessarily all referring to the same embodiment, nor are separate or alternative embodiments necessarily mutually exclusive of other embodiments. Moreover, various features are described which may be exhibited by some embodiments and not by others. Similarly, various requirements are described which may be requirements for some embodiments but may not be requirements for other embodiments. Reference will now be made in detail to embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

The reusable rockets and associate components described herein may be used for multiple launches and missions. For example, a rocket may be reused more than twenty launches, or more than fifty launches, etc. As such, it is desirable to reuse as many components of the rocket as possible to minimize the cost and turnaround time of missions. The rocket may include many different components, including a separation system for payloads and fairings. For the reusable rockets described herein, the separation system is able to release the payload and fairing from the upper stage of the rocket and survive reentry through the atmosphere. This allows the separation system to be used for multiple launches without refurbishment, or with minimal refurbishment. The separation system or components thereof may be cooled during reentry through the atmosphere. Example separation systems with these and other capabilities are described herein with respect to example rocket configurations. It is understood the separation system, components thereof, and/or methods of cooling may be used with different rocket configurations, to couple or release other components to the rocket, cool other components of the rocket, etc.

FIGS. 1A and 1B show an example embodiment of a second stage **100** (e.g., an upper stage) having a separation system **150**. The second stage **100** may be used with a first stage as part of a launch vehicle. The separation system **150** may be coupled to and/or form a forward end **102** (e.g., a nose cone) of the second stage **100**. FIG. 1A shows the second stage **100** without a payload **101**. FIG. 1B shows the second stage **100** with a payload **101** coupled to the second stage **100** via the separation system **150**, and a fairing **104** shown transparently for clarity. The second stage **100** and the separation system **150** are provided to complete multiple extraplanetary or orbital missions. Therefore, the second stage **100** and the separation system **150** are reusable for multiple missions.

During a launch mission, the second stage **100** is configured to be coupled with a first stage (e.g., a lower stage, not shown) of the launch vehicle. The first stage is configured for atmospheric launch operation to send the launch vehicle with the second stage **100** and the payload **101** to the upper atmosphere or lower earth orbit. The fairing **104** may be coupled to the second stage **100** and positioned over the payload **101** in order to protect (e.g., prevent or inhibit damage to) the payload **101**, the separation system **150** and/or the forward end **102** of the second stage **100** during

5

launch. The second stage **100** is configured to separate from the first stage to deliver the payload **101** to a planned orbit or trajectory. The separation system **150** is configured to release (e.g., separate, decouple, etc.) the payload **101** and the fairing **104** from the second stage **100** after the second stage **100** reaches one or more planned release locations along its path.

After the separation system **150** releases the payload **101** and the fairing **104** from the second stage **100**, the second stage **100** reenters the atmosphere and descends back to a planned landing location. When the second stage **100** reenters the atmosphere, atmospheric drag may heat the separation system **150** and any other components of the second stage **100**, e.g. to temperatures up to about 2,700 degrees Fahrenheit. The heat encountered during reentry to the atmosphere creates an environment that can cause typical rockets to oxidize, anneal, melt, and/or disintegrate. In accordance with the present disclosure, the separation system **150** and/or other components of the second stage **100** may be configured to survive and avoid such damage, and thus be reusable for multiple missions. The separation system **150** and/or other components of the second stage **100** may be configured to withstand reentry through the atmosphere so the separation system **150** and/or other components of the second stage **100** may be used for subsequent launches with minimal or no refurbishment, repair, etc. For example, after the second stage **100** lands, bolts, such as bolts **304**, may be removed from the body of release devices of the separation system **150**, such as body **302** of the release device **300**, and the bolts may be inspected. In order to reduce or minimize the time required to prepare the second stage **100** for the subsequent launch, a new set of bolts may be inserted into the body of the release devices for the subsequent launch while the removed bolts are inspected. Exposed surfaces of the body of the release devices and corresponding seals, such as seals **274**, may be inspected, without removing the body of the release devices from the vehicle. After inspections and any needed repairs or replacements are complete, the release devices of the separation system **150** are ready subsequent launches.

During reentry, the second stage **100** may be oriented so a longitudinal axis **103** of the second stage **100** is inclined at an angle with a direction of flight of the second stage **100** (e.g., an angle of attack). The second stage **100** may “belly flop” through the atmosphere during reentry. In some embodiments, such angle when the second stage **100** reenters the atmosphere may be about 50 degrees, about 55 degrees, about 60 degrees, about 65 degrees, about 70 degrees, about 75 degrees, about 80 degrees, about 85 degrees, about 90 degrees, about 95 degrees, about 100 degrees, about 110 degrees, about 120 degrees, about 130 degrees, about 140 degrees, about 150 degrees, about 160 degrees, about 170 degrees, about 180 degrees, and/or any value between any of the aforementioned values. In some embodiments, the angle when the second stage **100** reenters the atmosphere may be between about 50 degrees and about 100 degrees, or between about 60 degrees and about 90 degrees.

The second stage **100** may reorient as the second stage **100** descends through the atmosphere. After the second stage **100** reorients, the aforementioned angle between the longitudinal axis and the direction of travel may be about 30 degrees, about 35 degrees, about 40 degrees, about 45 degrees, about 50 degrees, about 55 degrees, about 60 degrees, about 65 degrees, about 70 degrees, about 75 degrees, about 80 degrees, about 85 degrees, about 90 degrees, about 95 degrees, and/or any value between any of

6

the aforementioned values. In some embodiments, after the second stage **100** reorients, the angle may be between about 30 degrees and about 95 degrees, or between about 40 degrees and about 85 degrees.

As the second stage **100** reenters the atmosphere and/or descends through the atmosphere, a windward side **108** of the second stage **100** (e.g., a side of the second stage **100** that at least partially faces the direction of flight) and of the separation system **150** (e.g., a windward side **108** of the forward end **102**) may be subjected to most or all of the atmospheric drag and resulting heat. Therefore, the windward side **108** of the second stage **100** and/or the separation system **150** may be configured to withstand the heat encountered upon reentry (e.g., heat generated by the atmospheric drag). The second stage **100** may include a heat shield **110** on the windward side **108** of the body of the second stage **100**. The separation system **150** may include a heat shield **152** positioned over at least a portion of the separation system **150**. The heat shields **110**, **152** may protect the second stage **100** and/or the separation system **150** and components thereof from the heat encountered upon reentry, as further described herein. The heat shield **110** and/or **152** may include carbon-carbon (e.g., reinforced carbon-carbon (RCC)), high-temperature refractory metals (e.g., steel, nickel-alloys, etc.), ceramic tiles, flexible blankets of high temperature textiles, low-density insulation materials (e.g., Saffil®), and/or any other suitable insulation materials. In some embodiments, the heat shield **110** and/or **152** may include a multi-layer insulation system including a plurality of suitable insulation materials. In some embodiments, the heat shield **110** and/or **152** may include a carbon-carbon outer layer and a Saffil® inner layer. In some embodiments, the insulation material of the heat shield **110** and/or **152** may be configured to withstand heat via ablation, and/or active cooling via a fluid (e.g., water, hydrogen, etc.) in a closed-loop system or an open-loop system. There may be no heat shield material directly covering the separation interface of the hardpoints, for example the top, exposed part of the release mechanisms. Those portions may be directly exposed to reentry plasma and protected by keeping the material temperature below the melting and oxidation temperature using a cooling system as described herein. The area around the hardpoints may be covered by thermal protection material that is several inches thick. There may be a carbon-carbon cylinder surrounding each hardpoint with redundant seals between the outer cylindrical face of the hardpoint and the carbon-carbon cylinder.

FIGS. 2A-2E illustrate various embodiments of a separation system **250** and/or components thereof. The separation system **250** may be used with a reusable rocket, such as the second stage **100**. The separation system **250** may be configured to secure and release a payload and a fairing. The separation system **250** may be configured to secure and release the payload via a payload release system **261A**. The separation system **250** may be configured to secure and release a fairing via a fairing release system **261B**. The separation system **250** may include a body **253** having a heat shield **252**.

As shown in FIG. 2A, the separation system **250** may include the body **253** extending between the payload release system **261A** and the fairing release system **261B**. The body **253** may be a forward end (e.g., a nose cone) of, or be coupled to a forward end, of the rocket. The body **253** may have a tubular, e.g. cylindrical, shape, and a conical shape. The body **253** may include an aft portion **254** and a forward portion **256**. The aft portion **254** may have a cylindrical shape or other tubular shape. The forward portion **256** of the

body **253** may have a conical shape, a truncated conical shape, a frustoconical shape or other tapered shape. The forward portion **256** may decrease in transverse width along the forward direction away from the rocket.

In some embodiments, the separation system **250** may include the payload release system **261A** and/or the fairing release system **261B**. The payload release system **261A** may be configured to couple (e.g., secure) a payload **201** to the separation system **250** (e.g., the body **253**), as shown in FIG. 2E. The fairing release system **261B** may be configured to couple (e.g., secure) a fairing **204** to the separation system **261B**.

In some embodiments, the payload release system **261A** and/or the fairing release system **261B** may include adaptors **266A**, **266B**. The payload release system **261A** may include a payload adaptor **266A** and/or the fairing release system **261B** may include a fairing adaptor **266B** (e.g., fairing frangible joint). In some embodiments, the payload adaptor **266A** and/or the fairing adaptor **266B** may include a tubular or ring shape. The payload adaptor **266A** may be coupled to the payload **201**. The fairing adaptor **266B** may be coupled to the fairing **204**, for example one or more panels forming the fairing. As shown in FIG. 2E, the payload adaptor **266A** may be coupled to a perimeter of an aft end **202** of the payload **201**. The payload adaptor **266A** may be coupled to a perimeter of an aft end **205** of the fairing **204**.

In some embodiments, the payload release system **261A** and/or the fairing release system **261B** may include one or more release devices **262** (for clarity, only some of which are labelled in FIG. 2A). The release devices **262** may be configured to couple (e.g., secure) the payload **201** and/or the fairing **204** to respective portions of the separation system **250**. The release devices **262** may be coupled to the body **253**. The release devices **262** may be positioned circumferentially around the forward portion **256** of the body **253**. Multiple release devices **262** may be circumferentially spaced around the body **253**. There may be at least four, at least five, at least six, at least seven, at least eight, at least nine, at least ten, at least eleven, at least twelve, at least thirteen, at least fourteen, at least fifteen, at least sixteen, at least seventeen, at least eighteen, at least nineteen, or at least twenty release devices **262** located within one or both of the payload release system **261A** and the fairing release system **261B**. In some embodiments, the first set of release devices **262A** may include a same number of, fewer, or more release devices **262** as the second set of release devices **262B**. The release devices **262** may all be identical to each other. The first set of release devices **262A** may be identical to each other, and/or the second set of release devices **262B** may be identical to each other. In some embodiments, some of the release devices **262** may have different dimensions to account for local structural differences in the body **253**. The release devices **262** may be evenly or unevenly spaced about the respective system. In some embodiments, a distance between the release devices **262** may be longer on a portion of the body **253** that faces a windward side of the second stage rocket than the distance between the release devices **262** on a portion of the body **253** that does not face the windward side of the second stage rocket. Accordingly, in some embodiments, the separation system **250** may include more release devices **262** on the portion of the body **253** that does not face the windward side of the second stage rocket.

In some embodiments, the release devices **262** may support other components of the separation system **250** on the rocket. The release devices **262** may be discrete points along the forward portion **256** of the body **253**, such as along the

heat shield. The heat shield may not be able to withstand the loads required to attach the payload **201** and/or the fairing **204**. Thus, the release devices **262** are required. In some embodiments each release device **262** may be configured to withstand loads (e.g., compression and/or tension) of at least 50 kips, at least 60 kips, at least 67 kips, at least 70 kips, or at least 80 kips.

In some embodiments, the adaptors **266A**, **266B** may not be configured to withstand point loads. As described above, the release devices **262** may be spaced apart. Therefore, if the release devices **262** were coupled directly to the adaptors **266A**, **266B**, the release devices **262** may apply point loads to the adaptors **266A**, **266B**. Accordingly, the payload release system **261A** may include a payload load spreader **264A** and/or the fairing release system **261B** may include a fairing load spreader **264B**. The payload load spreader **264A** and/or the fairing load spreader **264B** may include an aluminum alloy (e.g., 7050 Aluminum) and/or any other suitable material. The payload load spreader **264A** may be attached with the payload adaptor **266A**. The fairing load spreader **264B** may be attached with the fairing adaptor **266B**. The load spreaders **264A**, **264B** may have a tubular or ring shape. The release devices **262** may be coupled to the load spreaders **264A**, **264B** in order to couple the payload **201** and/or the fairing **204** to the separation system **250**. The release devices **262** may be distributed circumferentially along the respective load spreader **264A**, **264B**. The load spreaders **264A**, **264B** may be coupled to the adaptors **266A**, **266B** so the load spreaders **264A**, **264B** are positioned at least partially between the release devices **262** and the adaptors **266A**, **266B**. The release devices **262** may extend from fixed attachments with the body **253** of the separation system **250**, through openings in the load spreaders **264A**, **264B**, and releasably secure to a forward end of the load spreaders **264A**, **264B**.

The load spreaders **264A**, **264B** may convert (e.g., transform) the point loads applied by the release devices **262** to the load spreaders **264A**, **264B** into line loads. The load spreaders **264A**, **264B** may spread out or distribute this load and thus apply line loads to the adaptors **266A**, **266B**. The load spreaders **264A**, **264B** may spread the point loads applied by the release devices **262** around the adaptors **266A**, **266B** so portions of the adaptors **266A**, **266B** aligned with the release devices **262** are not subjected to substantially larger loads than other portions of the adaptors **266A**, **266B** that are not aligned with the release devices **262**. Therefore, the load spreaders **264A**, **264B** may allow the release devices **262** to couple with adaptors **266A**, **266B** that are not specifically designed to be used with the separation system **250** and/or the release devices **262**. In this way, a variety of different adaptors, such as custom adaptors for a given payload, may be used with the separation system.

In some embodiments, the release devices **262** may decouple from the load spreaders **264A**, **264B** to thereby release the payload **201** and/or the fairing **204** from the separation system **250** once the second stage rocket reaches one or more planned release points. The load spreaders **264A**, **264B** and the adaptors **266A**, **266B** may remain coupled to the respective payload **201** and the fairing **204** after the release devices **262** decouple from the respective load spreaders **264A**, **264B**. Accordingly, the load spreaders **264A**, **264B** and the adaptors **266A**, **266B** may not be coupled to the separation system **250** when the second stage rocket reenters the atmosphere.

In some embodiments, the payload release system **261A** may include a first set (e.g., plurality) of the release devices **262A**. The fairing release system **261B** may include a

9

second set (e.g., plurality) of the release devices **262B**. In some embodiments, the first set of release devices **262A** may be distributed (e.g., spaced) around the body **253** so the first set of release devices **262A** form a ring of release devices **262** around the body **253**. In some embodiments, the second set of release devices **262B** may be distributed (e.g., spaced) around the body **253** so the second set of release devices **262B** form a ring of release devices **262** around the body **253**. The first set of release devices **262A** may be positioned forward of the second set of release devices **262B**. The first set of release devices **262A** may be positioned at least partially between the second set of release devices **262B** and a forward end **253A** of the body **253**. The second set of release devices **262B** may be positioned aft of (e.g., rearward) the first set of release devices **262A**. The second set of release devices **262B** may be positioned at least partially between the first set of release devices **262A** and an aft end **253B** of the body **253**. The first set of release devices **262A** may be circumferentially distributed around the body **253** at the forward end **253A** of the body **253** and configured to retract into the body **253**, as further described. The second set of release devices **262B** may be circumferentially distributed around the body **253** at an aft end **256B** of the forward portion **256** of the body **253** and configured to retract into the body **253**, as further described.

In some embodiments, the first set of release devices **262A** may be coupled to the payload load spreader **264A** to secure the payload load spreader **264A** with the body **253**. The payload load spreader **264A** may be coupled to the payload adaptor **266A** so the payload load spreader **264A** is positioned at least partially between the payload adaptor **266A** and the first set of release devices **262A**. The second set of release devices **262B** may be coupled to the fairing load spreader **264B** to secure the fairing load spreader **264B** to the body **253**. The fairing load spreader **264B** may be coupled to the fairing adaptor **266B** so the fairing load spreader **264B** is positioned at least partially between the fairing adaptor **266B** and the second set of release devices **262B**. The release devices **262** may extend through the respective load spreader **264A**, **264B**, as further described.

The first set of release devices **262A** may decouple from the payload load spreader **264A** after the second set of release devices **262B** decouple from the fairing load spreader **264B** and the fairing has separated and fallen away (or actively jettisoned away in some embodiments) from the rocket. In some embodiments, the first set of release devices **262A** and the second set of release devices **262B** may decouple from the payload load spreader **264A** and the fairing load spreader **264B** simultaneously.

As shown in FIG. 2B, the separation system **250** may include the heat shield **252**. The heat shield **252** may be coupled to the body **253** of the separation system **250**. The heat shield **252** may be positioned over the body **253** so the heat shield **252** covers the aft portion **254** and the forward portion **256**. The heat shield **252** may protect the body **253**, the release devices **262**, and/or any other components of the separation system **250** from heat generated upon reentry of the second stage rocket through the atmosphere. The heat shield **252** may include any suitable thermal protection system (TPS) materials. The heat shield **252** may include carbon-carbon (e.g., reinforced carbon-carbon (RCC)), high-temperature refractory metals (e.g., steel, nickel-alloys, etc.), ceramic tiles, flexible blankets of high temperature textiles, low-density insulation materials (e.g., Saffil®), and/or any other suitable insulation materials. In some embodiments, the heat shield **252** may include a multi-layer insulation system including a plurality of suitable insulation

10

materials. In some embodiments, the heat shield **252** may include a carbon-carbon outer layer and a Saffil® inner layer. In some embodiments, the insulation material of the heat shield **252** may be configured with withstand heat via ablation, and/or active cooling via a fluid (e.g., water, hydrogen, etc.) in a closed-loop system or an open-loop system. The heat shield **252** may be reusable so the heat shield **252** may be used in a first launch mission and one or more subsequent launch missions.

FIG. 2C is a cross-sectional side view of a schematic of part of an embodiment of a separation system **250** that may be used with the separation system. FIG. 2D is a side view of a schematic of a portion of an embodiment of the separation system **250**, including embodiments of the release device **262**, a standoff **267**, a seal **274**, and part of the heat shield **252**. As shown in FIGS. 2C and 2D, in some embodiments, the heat shield **252** may include openings **270** extending therethrough. The release devices **262** may extend partially or completely through the openings **270**. Accordingly, the load spreaders **264A**, **264B** and/or the adaptors **266A**, **266B** may be positioned external to (e.g., outside) the heat shield **252**. Therefore, the heat shield **252** may not prevent or inhibit the load spreaders **264A**, **264B** and/or the adaptors **266A**, **266B** from separating from the separation system **250** when the release devices **262** decouple from the load spreaders **264A**, **264B**.

As shown in FIG. 2D, in some embodiments, the release devices **262** may be coupled to the load spreaders **264A**, **264B** via standoffs **267**. Each standoff **267** may be releasably coupled to a respective one of the release devices **262** and coupled with the respective the load spreaders **264A**, **264B**. The standoffs **267** may be positioned between the release devices **262** and the load spreaders **264A**, **264B**. In some embodiments, the standoffs **267** may be attached to or integrated with the load spreaders **264A**, **264B**. The standoffs **267** may be downward projecting portions of the respective load spreaders **264A**, **264B**. The release devices **262** may contact and releasably connect with openings in the standoffs **267** in order to align and couple (e.g., secure) the load spreaders **264A**, **264B** to the separation system **250** (e.g., to the body **253**), as further described. The standoffs **267** may position the load spreaders **264A**, **264B** a distance **272** from the release devices **262**. Therefore, in some embodiments, the standoffs **267** may allow a forward end **263** of the release devices **262** to be positioned at least partially in the opening **270** of the heat shield **252** below an outer surface **252A** of the heat shield **252**. Accordingly, the heat shield **252** may help to protect the release devices **262** from heat encountered upon reentry of the second stage rocket through the atmosphere (e.g., heat generated by atmospheric drag).

In some embodiments, the seal **274** may be positioned between the release devices **262** and the heat shield **252**. The seal **274** may prevent or inhibit heat encountered upon reentry of the second stage rocket through the atmosphere from passing through an annular gap **278** formed between the release devices **262** and the heat shield **252**. The seal **274** may be a ring-like structure. There may be one or more of the seals **274**. The seal **274** may include a high temperature rope seal, a high temperature compound material, and/or any other suitable sealing material. In some embodiments, the seal **274** may include a high temperature rope seal including Saffil® wrapped with an Inconel mesh.

FIG. 2E is a close-up side view of the schematic of the separation system **250** of FIG. 1B supporting an example payload **201** and an example fairing **204** (for clarity, the fairing **204** is shown transparently). As shown in FIG. 2E, in

11

some embodiments, the separation system **250** may include a skirt **269**. The skirt **269** may be positioned over at least a portion of the body **253** and/or the heat shield **252**. In some embodiments, the skirt **269** may be positioned over the aft portion **254** and/or the forward portion **256** of the body **253**. The skirt **269** may be positioned aft (e.g., rearward) of the fairing release system **261B**. In some embodiments, the skirt **269** may be coupled to the fairing load spreader **264B**. Accordingly, when the second set of release devices **262B** decouple from the fairing load spreader **264B**, the skirt **269** may remain coupled to the fairing load spreader **264B** so the skirt **269** may decouple from the separation system **250** (e.g., the body **253**).

In some embodiments, the skirt **269** may reduce or minimize an aerodynamic drag of the separation system **250** when the fairing load spreader **264B** is coupled to the separation system **250** via the second set of release devices **262B**. The skirt **269** may cover the gap **276** (shown in FIG. 2D) between the fairing load spreader **264B** and the heat shield **252**. In some embodiments, the skirt **269** may include ventilation (e.g., one or more vents) so a pressure between the skirt **269** and the heat shield **252** can equalize with a pressure outside of the skirt **269**. Accordingly, the ventilation may prevent or inhibit formation of a pressure differential across the skirt **269**.

In some embodiments, the separation system **250** may include a barrier (e.g., particulate barrier) **265**. The barrier **265** may be positioned over the heat shield **252** between the payload release system **261A** and the fairing release system **261B** (e.g., between the payload load spreader **264A** and the fairing load spreader **264B**). The barrier **265** may isolate the payload **201** and/or the fairing **204** from the heat shield **252** to prevent or inhibit particles or contaminants from a portion of the heat shield **252** between the payload release system **261A** and the fairing release system **261B** from contacting the payload **201** and/or the fairing **204**. In some embodiments, the barrier **265** may be coupled to the payload load spreader **264A** and/or the fairing load spreader **264B** so the barrier **265** remains coupled to the payload load spreader **264A** and/or the fairing load spreader **264B** after the release devices **262** decouple from the load spreaders **264A**, **264B**.

In some embodiments, the release devices **262** and/or the release systems **261A**, **261B** may include a cooling system. The cooling system may be configured to cool the release devices **262** and/or other components of the release systems **261A**, **261B** during reentry of the separation system **250** and/or a reusable second stage rocket through the atmosphere, as further described herein.

FIGS. 3A-4H illustrate various embodiments of a release device **300** for use in a release system, such as the payload release system **261A** and/or the fairing release system **261B**. Each release system may include a plurality of the release devices **300**. The same release device **300** may be used in both the payload release system **261A** and/or the fairing release system **261B**. In some embodiments, the same basic design for the release device **300** may be used in both release systems **261A**, **261B** but with different shapes, dimensions, etc., for example for the particular payload and fairing being used. In some embodiments, different embodiments of the release device **300** may be used for each release system **261A**, **261B**, or even within the same release system. The release device **300** may have the same or similar features as the release device **262**, and vice versa, except as otherwise described.

FIG. 3A is a cross-sectional view of the release device **300** (e.g., hardpoint). As shown in FIG. 3A, the release device **300** may include a body **302** and a bolt **304**. The release

12

device **300** may act as a combined reusable compression pad and release mechanism. In some embodiments, the body **302** includes an elongated tubular shape. The body **302** may define a channel **310** extending axially or longitudinally through the body **302**. The channel **310** may extend along a longitudinal axis **303** extending between a proximal end **302A** of the body **302** and a distal end **302B** of the body **302**. The bolt **304** may be positioned in the channel **310**.

The bolt **304** may include an elongated shaft **312** and a head **314**. The shaft **312** may be positioned in the channel **310** so the shaft **312** extends longitudinally through the channel **310**. The head **314** may be positioned at a distal end **312B** of the shaft **312**. In some embodiments, the bolt **304**, the shaft **312** and/or the head **314** may be formed of titanium, tungsten, other suitable materials, or combinations thereof. The head **314** may contact a corresponding structure such as a standoff (not shown in FIG. 3A), to secure a component (such as a load spreader) with the rocket, as further described.

In some embodiments, the body **302** may include a base **309**, such as a flange or lip. The base **309** may extend transversely or radially outward from the body **302**. The base **309** may be coupled with the rocket, e.g., a bracket or support, or to a body of the separation system or nose cone. In some embodiments, one or more fasteners **309A**, such as a series of bolts as shown in FIG. 3D, may be inserted through the base **309** to couple the base **309** with the rocket.

FIGS. 3B and 3C are cross-sectional views of the release device **300** shown respectively in extended (or secured) and retracted (or released) positions. In some embodiments, as shown in FIGS. 3B and 3C, the bolt **304** may be configured to translate through the channel **310** between an extended position **308** and a retracted position **306**. When releasing a component, the bolt **304** may translate through the channel **310** towards the proximal end **302A** of the body **302** to move from the extended position **308** to the retracted position **306**. When being secured with a component, the bolt **304** may translate through the channel **310** towards the distal end **302B** of the body **302** to move from the retracted position **306** to the extended position **308**.

As shown in FIG. 3B, when the bolt **304** is in the extended position **308**, the bolt **304** may be positioned so the shaft **312** partially extends distally out of the channel **310** beyond the distal end **302B** of the body **302**. Accordingly, the head **314** may be positioned distally of and outside of the channel **310**. In some embodiments, the head **314** may be configured to engage with a portion of a connector **301** for a component, which may be a payload connector (e.g., a payload adaptor **266A**, a payload load spreader **264A** or a standoff **267**) or a fairing connector (e.g., a fairing adaptor **266B**, a fairing load spreader **264A** or a standoff **267**). In some embodiments, the connector **301** may include a slot **301A**. In some embodiments, the head **314** may be configured to extend into the slot **301A** when the bolt **304** is in the extended position **308**.

As shown in FIG. 3C, when the bolt **304** is in the retracted position **306**, the head **314** may be positioned in the channel **310**. In some embodiments, the channel **310** may include a recess **311** at the distal end **302B** of the body **302**. The recess **311** may be configured to receive the head **314** of the bolt **304**. In some embodiments, the recess **311** may include a portion of the channel **310** that may be wider than the rest of the channel **310**. The head **314** may be positioned in the recess **311** when the bolt **304** is in the retracted position **306**. In some embodiments, a proximal end **312A** of the shaft **312** may extend out of the channel **310** past a proximal end **302A** of the body **302** when the bolt **304** is in the retracted position **306** and/or the extended position **308**. The bolt **304** may

13

retract after being rotated to allow the head **314** to be received in the recess **311**, as further described.

In some embodiments, the release device **300** may include a biasing member **305**. The biasing member **305** may include a spring. The biasing member **305** may be coupled to the shaft **312**. The biasing member **305** may proximally bias the bolt **304** so the bolt **304** is biased towards the retracted position **306**. The bolt **304** may be biased but not translate until after being rotated.

FIGS. 3D-3G are top perspective views of the release device **300** sequentially illustrating the bolt rotating from a first rotational position **320** to a second rotational position **322** and translating from the extended position **308** to the retracted position **306**. As shown in FIGS. 3D-3G, the bolt **304** may be configured to be rotated about the longitudinal axis **303** between the first rotational position **320** (FIG. 3D) and the second rotational position **322** (FIG. 3F). The bolt **304** may have an intermediate rotational position or positions, such as that shown in FIG. 3E. The bolt **304** may be configured to rotate from the first rotational position **320** to the second rotational position **322** in a first rotational direction **323**, for example when releasing the component. The bolt **304** may retract into the release device **300**, as described, with the bolt **304** in the second rotational position **322**, as shown in FIG. 3G. The bolt **304** may be configured to rotate from the second rotational position **322** to the first rotational position **320** in an opposite, second rotational direction **324**, for example when being secured with the component.

In some embodiments, the bolt **304** may be axially tensioned in the extended position **308** when securing the component. When the bolt **304** is in the first rotational position **320**, the head **314** may be configured to engage with, for example contact, and apply a pressure onto a seat **301B** (shown in FIG. 3B) of the connector **301**. The seat **301B** may be a bottom surface of the recess **311**. In some embodiments, a proximal surface **314A** of the head **314** may be configured to engage with the seat **301B**. When the bolt **304** is in the second rotational position **322**, and/or while being rotated from the first rotational position **320** to the second rotational position **322**, the bolt **304** may be configured to disengage with the seat **301B** of the connector **301**. The proximal surface **314A** and the seat **301B** may have corresponding contours to facilitate rotation of the head **314** and disengagement from the connector **301**, as further described.

In some embodiments, as shown in FIGS. 3B and 3C, the release device **300** may include an actuator **326**. The actuator **326** may be configured to rotate the bolt **304** between the first rotational position **320** and the second rotational position **322**. In some embodiments, the actuator **326** may be coupled to or extend from the shaft **312** of the bolt **304**. Accordingly, the actuator **326** may be configured to rotate the shaft **312** of the bolt **304**. In some embodiments, the actuator **326** may be positioned proximally to the body **302**. The actuator **326** may be coupled to a portion of the shaft **312** that extends out of the channel **310** of the body **302** past the proximal end **302A** of the body **302**. The actuator **326** may include a transverse actuation arm and/or any other actuator configured to rotate the bolt **304** between the first rotational position **320** and the second rotational position **322**. The bolt **304** may be rotationally biased (e.g., pre-tensioned) towards the first rotational position **320** to prevent or inhibit rotation of the bolt **304** in the first rotational direction **323** without the actuator **326** rotating the bolt **304** in the first rotational direction **323**.

14

As shown in FIGS. 3B-3D, the head **314** of the bolt **304** and the slot **301A** of the connector **301** may have corresponding shapes or planforms. The head **314** and slot **301A** may be elongated. The head **314** may include a length **316** and a width **318**. The length **316** may include a distance across the head **314** in a first direction and the width **318** may include a distance across the head **314** in a second direction transverse to (e.g. perpendicular to) the length **316**. The length **316** of the head **314** may be greater than the width **318** of the head **314**. In some embodiments, the length **316** of the head **314** may include a distance of about 1.0 inch, about 1.5 inches, about 2.0 inches, about 2.5 inches, about 3.0 inches, about 3.5 inches, about 4.0 inches, about 4.5 inches, about 5.0 inches, about 5.5 inches, about 6.0 inches, about 6.5 inches, about 7.0 inches, about 7.5 inches, about 8.0 inches, about 8.5 inches, about 9.0 inches, about 9.5 inches, about 10.0 inches, and/or any value between the aforementioned values. In some embodiments, the width **318** of the head **314** may include a distance of about 0.5 inches, about 1.0 inch, about 1.5 inches, about 2.0 inches, about 2.5 inches, about 3.0 inches, about 3.5 inches, about 4.0 inches, about 4.5 inches, about 5.0 inches, about 5.5 inches, about 6.0 inches, about 6.5 inches, about 7.0 inches, about 7.5 inches, about 8.0 inches, about 8.5 inches, about 9.0 inches, about 9.5 inches, and/or any value between the aforementioned values.

In some embodiments, when the bolt **304** is in the first rotational position **320**, the head **314** may extend across the slot **301A** of the connector **301**. Accordingly, the length **316** of the head **314** may be positioned transverse to a direction of elongation of the slot **301A**, so that the seat **301B** engages with and prevents axial translation of the head **314**. In some embodiments, when the bolt **304** is in the second rotational position **322**, the head **314** may align with the slot **301A**. Accordingly, the length **316** of the head **314** may be aligned with the elongated dimension of the slot **301A** so that the head **314** may translate out of the slot **301A**, releasing the component.

In some embodiments, the recess **311** of the channel **310** may include a cross-sectional shape similar to that of the head **314**. Accordingly, the recess **311** may be elongated, with a longer length and shorter width. When the bolt **304** is in the first rotational position **320**, the head **314** may be positioned so the length **316** of the head **314** extends transverse to the direction of elongation of the recess **311**, as shown in FIG. 3D. When the bolt **304** is in the second rotational position **322**, the length **316** of the head **314** may be aligned with the elongated dimension of the recess **311**, as shown in FIG. 3F. Accordingly, as shown in FIGS. 3F and 3G, the bolt **304** may translate from the extended position **308** to the retracted position **306** when the bolt **304** is in the second rotational position **322**. The head **314**

The head **314** and seat **301B** may have correspondingly contoured surfaces to facilitate rotational disengagement. As shown in FIG. 3H, in some embodiments, the proximal surface **314A** of the head **314** may be helical. In some embodiments, the head **314** may include proximal protrusions **330** forming the proximal surface **314A** of the head **314**. The proximal surface **314A** may define a partial or incomplete thread. The proximal surface **314A** may include a first surface **331** and an opposite second surface **332**, with each being helical to engage corresponding helical contours of the seat **301B**. In some embodiments, the proximal surface **314A** may be sloped or ramped, such as a linear surface. For example, the proximal surface **314A** may form an angle **333** with a horizontal axis **334** that extends transverse to the longitudinal axis of the shaft. The angle **333** may be no more than 5 degrees, no more than 10 degrees, no

15

more than 15 degrees, no more than 20 degrees, no more than 25 degrees, no more than 30 degrees, no more than 35 degrees, no more than 40 degrees, no more than 45 degrees.

The corresponding surface of the seat **301B** of the connector **301** that contacts the proximal surface **314A** may include a corresponding contour. The seat **301B** may have a same shape as that of the protrusions **330**. The seat **301B** may thus be helical, curved, ramped, etc. Accordingly, when the head **314** engages with the seat **301B** in the first rotational position **320**, the proximal surface **314A** may engage with the seat **301B** to prevent or inhibit the bolt **304** from rotating in the second rotational direction **324** but may allow or facilitate the bolt **304** to rotate in the first rotational direction **323**. The axial tension applied to the bolt **304** may in effect cause the proximal surface **314A** to “slide down” the corresponding contour of the seat **301B**.

FIGS. 4A and 4B illustrate a cooling system **400** that may be used with the release device **300**. The cooling system **400** may be configured to cool the release device **300** during reentry of the rocket through the atmosphere. As shown in FIG. 4A, the body **302** may include a first cooling assembly **402** of the cooling system **400**, and the bolt **304** may include a second cooling assembly **410** of the cooling system **400**.

In some embodiments, the first cooling assembly **402** may include a first channel **404** and a second channel **406**. The first channel **404** may extend axially through the body **302** of the release device **300** from the distal end **302B** to the proximal end **302A** of the body **302**. A proximal end **404A** of the first channel **404** may be positioned proximally to the proximal end **302A** of the body **302**. The first channel **404** may extend out of the body **302** past the proximal end **302A** of the body **302**. In some embodiments, the second channel **406** may be an annular (e.g., ring shaped) channel. The second channel **406** extends circumferentially around a central longitudinal axis of the body **302**. The second channel **406** may be positioned at the distal end **302B** of the body **302** so that the second channel **406** extends around the recess **311** of the channel **310**. In some embodiments, the second channel **406** may extend around the channel **310**. In some embodiments, the second channel **406** may be coupled to and/or in fluid communication with a distal end **404B** of the first channel **404**.

In some embodiments, the first channel **404** may be coupled to and/or in fluid communication with a circulation system **401**. The circulation system **401** may be configured to pump a coolant through the first channel **404** and to and through the second channel **406**. As the coolant flows through the second channel **406**, the coolant draws heat away from (cools) the distal end **302B** of the body **302**.

In some embodiments, the second cooling assembly **410** may be positioned at least partially within the bolt **304**. The second cooling assembly **410** may include a channel **412** and a recess **414**. The channel **412** may extend axially through the shaft **312** of the bolt **304** from the proximal end **312A** of the shaft **312** of the bolt **304**. The recess **414** may extend through the head **314** of the bolt **304**. The channel **412** may be coupled to and/or in fluid communication with the recess **414**. In some embodiments, the channel **412** may be coupled to and/or in fluid communication with the circulation system **401**, and/or a different circulation system. The circulation system **401** may be configured to pump a fluid, such as a coolant, into the recess **414** via the channel **412**. The coolant may draw heat away from (cool) the head **314** of the bolt **304**. In some embodiments, a fluid may be pumped to the recess **414** and exit the system at the head **314**, as further described.

16

In some embodiments, the body **302** may include a material configured to transfer heat to the recess **414** in order to increase or maximize heat transfer to the coolant. The body **302** may include aluminum and/or any other thermally conductive material.

As shown in FIG. 4B, in some embodiments, the second cooling assembly **410** may include a cap **416**. The cap **416** may include a plurality of channels **418** extending through the cap **416**. The plurality of channels **418** may extend from a proximal end **416A** of the cap **416** to a distal end **416B** of the cap **416**. The cap **416** may be coupled to the head **314** of the bolt **304** at a distal end **314B** of the head **314**. The cap **416** may be coupled to the head **314** so the plurality of channels **418** align with the recess **414**.

In some embodiments, coolant **420** or other fluid in the recess **414** may be configured to boil when the coolant **420** is exposed to heat. In some embodiments, coolant **420** in the plurality of channels **418** may be configured to boil when the coolant **420** in the plurality of channels **418** is exposed to heat. The coolant **420** may draw in heat from (e.g., cool) the head **314** and/or the cap **416**, or other portions of the bolt **304** or system. At least a portion of the coolant **420** in the recess **414** and/or the plurality of channels **418** may phase change to vapor **422** when a fluid portion of the coolant **420** boils. The coolant **420** may be configured to boil at a temperature below a melting or annealing temperature of the surrounding structure, such as that of the head **314** and/or the bolt **304**. Accordingly, the fluid portion of the coolant **420** in the recess **414** and/or the plurality of channels **418** may remain below or at a boiling temperature of the coolant **420** when a temperature around the coolant **420** and/or the head **314** is above the boiling temperature of the coolant **420**. Accordingly, the coolant **420** may prevent or inhibit a temperature of the head **314** and/or the cap **416** from raising above the boiling temperature of the coolant **420** and/or a melting or annealing temperature of the head **314**, the bolt **304**, and/or the cap **416**. In some embodiments, the vapor **422** and/or heat in the coolant **420** may exit the recess **414** and/or the channels **418** by flowing through the plurality of channels **418** in the cap **416** and being injected to an exterior of the cap **416**. When a fluid portion of the coolant **420** is heated and/or phase changes to vapor **422**, the coolant **420** may expand causing the vapor **422** to be forced through the plurality of channels **418**. In some embodiments, the coolant **420** may include water and/or any other liquid configured to boil at a temperature below a melting or annealing temperature of the head **314** and/or the bolt **304**. In this manner, the vapor **422** exterior to the system may provide a vaporous heat shield between plasma and upper, exposed portions of the release device **300** (e.g., the head **314**, the bolt **303**, the body **302**, etc.).

In some embodiments, the cap **416** may include a material configured to transfer heat to the recess **414** in order to increase or maximize heat transfer to the coolant **420**. The cap **416** may include copper, aluminum, and/or any other material with a high thermal diffusivity.

As shown in FIG. 4A, in some embodiments, the body **302** may include an end cap **424**. The end cap **424** may include the second channel **406**. The end cap **424** may include any features and/or functions of the cap **416** (see FIG. 4B). As coolant (e.g., coolant **420** in FIG. 4B) flows through the second channel **406** in the end cap **424**, the coolant may draw in heat from (e.g., cool) the body **302** and/or the end cap **424**. At least a portion of the coolant in the second channel **406** may phase change to vapor when a fluid portion of the coolant boils. The coolant may be configured to boil at a temperature below a melting or

17

annealing temperature of the surrounding structure, such as that of the body **302** and/or the end cap **424**. Accordingly, the fluid portion of the coolant in the second channel **406** may remain below or at a boiling temperature of the coolant when a temperature around the coolant and/or the body **302** is above the boiling temperature of the coolant. Accordingly, the coolant may prevent or inhibit a temperature of the body **302** from raising above the boiling temperature of the coolant and/or above a melting or annealing temperature of the body **302**. In some embodiments, the vapor and/or heat in the coolant may exit the second channel **406** by flowing through a plurality of channels (e.g., channels **418** in FIG. **4B**) in the end cap **424** and being injected or otherwise emitted to an exterior of the end cap **424**. In this manner, the vapor exterior to the system may provide a vaporous heat shield between plasma and the release device **300** (e.g., the heat **314**, the bolt **303**, the body **302**, etc.).

FIGS. **5A** and **5B** illustrate schematics of cooling systems **500A** and **500B** that may be used with any of the release devices and systems described herein, such as those described with respect to FIGS. **2A-4B**. In some embodiments, the cooling system **500A** may include an active cooling system. In some embodiments, the cooling systems **500B** may include a passive cooling system.

As shown in FIG. **5A**, the cooling system **500A** may include a circulation system **501A** coupled to a plurality of release mechanisms **502A**, which may be any of the release devices herein, for example the release devices as shown and described with respect to FIGS. **2A-4B**. The circulation system **501A** may be used in a closed loop for recirculating coolant, such as with the cooling system **400** of FIG. **4A**. The circulation system **501A** may include a first flow path **503A** and a second flow path **533A**. Coolant may be circulated through the first flow path **503A** to the plurality of release mechanisms **502A**. As the coolant flows through the plurality of release mechanisms **502A**, the coolant may draw heat away from (e.g., cool) the plurality of respective release mechanisms **502A**. The coolant may be circulated through the first flow path **503A** from the plurality of release mechanisms **502A** to a heat exchanger **520A**. After the coolant passes through the heat exchanger **520A**, the coolant may be circulated through the first flow path **503A** back to the plurality of release mechanisms **502A**.

In some embodiments, coolant may be circulated through the heat exchanger **520A** through the second flow path **533A**. The coolant in the second flow path **533A** may enter the heat exchanger **520A** at a lower temperature than a temperature of the coolant in the first flow path **503A** when the coolant in the first flow path **503A** enters the heat exchanger **520A**. Accordingly, the heat exchanger **520A** may transfer heat from the coolant in the first flow path **503A** to the coolant in the second flow path **533A** in order to cool the coolant in the first flow path **503A**.

In some embodiments, the circulation system **501A** may include a first cooling pump **521A** and a first circulation pump **522A**. The first cooling pump **521A** may be configured to pump the coolant through the first flow path **503A** during reentry of a rocket (e.g., the second stage **100**) through the atmosphere. The first cooling pump **521A** may be configured to pump the coolant through the first flow path **503A** to provide the coolant to the plurality of release mechanisms **502A** in order to cool the plurality of release mechanisms **502A**. The first circulation pump **522A** may be configured to circulate the coolant through the first flow path **503A** when the rocket (e.g., the second stage **100**) is in orbit in order to prevent or inhibit the coolant from freezing in supply lines of the cooling system **500A**. The first cooling

18

pump **521A** may be a larger pump than the first circulation pump **522A**. Accordingly, the first cooling pump **521A** may be configured to generate a higher flow rate of coolant through the first flow path **503A** than the first circulation pump **522A**.

In some embodiments, the circulation system **501A** may include a second cooling pump **541A** and a second circulation pump **542A**. The second cooling pump **541A** may be configured to pump the coolant through the second flow path **533A** during reentry of the rocket (e.g., the second stage **100**) through the atmosphere. The second cooling pump **541A** may be configured to pump the coolant through the second flow path **533A** to provide the coolant to the heat exchanger **520A** at a flow rate high enough to draw heat away from the coolant in the first flow path **503A**. The second circulation pump **542A** may be configured to circulate the coolant through the second flow path **533A** when the rocket (e.g., the second stage **100**) is in orbit in order to prevent or inhibit the coolant from freezing in supply lines of the cooling system **500A**.

The first flow path **503A** may include a first gas line **506A** and/or a first coolant tank **508A**. The first gas line **506A** may be configured to provide pressurized gas to the first coolant tank **508A** in order to pressurize the first coolant tank **508A** and the coolant in the first flow path **503A**. Pressurizing the first coolant tank **508A** and the coolant in the first flow path **503A** may prevent or inhibit the coolant in the first flow path **503A** from changing phases when the coolant is heated or cooled. The first flow path **503A** may include a first regulator **509A** configured to regulate the pressure of the pressurized gas. The pressurized gas may include helium and/or any other suitable gas. The first regulator **509A** may be set at a pressure of about 20 psia, about 30 psia, about 40 psia, about 45 psia, about 50 psia, about 55 psia, about 60 psia, and/or any value between the aforementioned values.

The second flow path **533A** may include a second gas line **536A** and/or a second coolant tank **538A**. The second gas line **536A** may be configured to provide pressurized gas to the second coolant tank **538A** in order to pressurize the second coolant tank **538A** and the coolant in the second flow path **533A**. Pressurizing the second coolant tank **538A** and the coolant in the second flow path **533A** may prevent or inhibit the coolant in the second flow path **533A** from changing phases when the coolant is heated or cooled. The second flow path **533A** may include a second regulator **539A** configured to regulate the pressure of the pressurized gas. The pressurized gas may include helium and/or any other suitable gas. The second regulator **539A** may be set at a pressure of about 5 psia, about 10 psia, about 15 psia, about 20 psia, about 30 psia, about 40 psia, about 45 psia, and/or any value between the aforementioned values. The first regulator **509A** may be set to a higher pressure than the second regulator **539A**.

In some embodiments, the first flow path **503A** may include a first air line **504A** and a first coolant line **505A**. The first air line **504A** may include a valve **514A**. The valve **514A** may include a manual valve configured to be manually opened/closed. The valve **514A** may include a normally closed valve. The valve **514A** may be opened during ground processing (e.g., refurbishment) to prepare the cooling system **500A** for a subsequent launch mission. When the valve **514A** is opened, the first air line **504A** may purge (e.g., drain) the coolant from the first flow path **503A**. The first coolant line **505A** may include a valve **515A**. The valve **515A** may include a manual valve configured to be manually opened/closed. The valve **515A** may be opened during ground processing (e.g., refurbishment) to prepare the cool-

19

ing system **500A** for a subsequent launch mission. The valve **515A** may be opened during ground processing in order to provide coolant to the first flow path **503A**. The valve **515A** may include a normally closed valve. The first gas line **506A** may include a valve **516A**. The valve **516A** may include an electronic valve. The valve **516A** may include a normally closed valve.

In some embodiments, the second flow path **533A** may include a second air line **534A** and a second coolant line **535A**. The second air line **534A** may include a valve **544A**. The valve **544A** may include a manual valve configured to be manually opened/closed. The valve **544A** may include a normally closed valve. The valve **544A** may be opened during ground processing (e.g., refurbishment) to prepare the cooling system **500A** for a subsequent launch mission. When the valve **544A** is opened, the second air line **534A** may purge (e.g., drain) the coolant from the second flow path **533A**. The second coolant line **535A** may include a valve **545A**. The valve **545A** may include a manual valve configured to be manually opened/closed. The valve **545A** may be opened during ground processing (e.g., refurbishment) to prepare the cooling system **500A** for a subsequent launch mission. The valve **545A** may be opened during ground processing in order to provide coolant to the second flow path **533A**. The valve **545A** may include a normally closed valve. The second gas line **536A** may include a valve **546A**. The valve **546A** may include an electronic valve. The **546A** may include a normally closed valve.

As shown in FIG. **5B**, the cooling system **500B** may include a circulation system **501B** coupled to a plurality of release mechanisms **502B**, which may be any of the release devices herein, for example the release devices as shown and described with respect to FIGS. **2A-4B**. The circulation system **501A** (of FIG. **5A**) may be used in an “open loop” where coolant is expelled from the cooling system **500B**, such as with the cooling assembly **410** of FIG. **4B**. The circulation system **501B** of FIG. **5B** may include a flow path **503B**. In some embodiments, the coolant may be conveyed to the plurality of release mechanisms **502B** via the flow path **503B**. The flow path **503B** may be thermally conditioned to prevent or inhibit icing in the flow path **503B** and/or the cooling system **500B**. In some embodiments, the coolant may draw heat away from a bolt of each release mechanism of the plurality of release mechanisms **502B**. In some embodiments, the coolant may boil to prevent or inhibit a temperature of a bolt of each of the plurality of release mechanisms **502B** from increasing to a melting or annealing temperature of the bolt. The vapor coolant may then exit the release mechanisms **502B** through channels in the release mechanisms **502B** that are open to the atmosphere and/or plasma around a rocket during reentry through the atmosphere, as described herein.

In some embodiments, the flow path **503B** may include an air line **504B**, a coolant line **505B**, and a gas line **506B**. The air line **504B** may include a valve **514B**. The valve **514B** may include a manual valve configured to be manually opened/closed. The valve **514B** may include a normally closed valve. The valve **514B** may be opened during ground processing (e.g., refurbishment) to prepare the cooling system **500B** for a subsequent launch mission. When the valve **514B** is opened, the air line **504B** may purge (e.g., drain) the coolant from the first flow path **503A**. The coolant line **505B** may include a valve **515B**. The valve **515B** may include a manual valve configured to be manually opened/closed. The valve **515B** may include a normally closed valve. The valve **515B** may be opened during ground processing (e.g., refurbishment) to prepare the cooling system **500A** for a subse-

20

quent launch mission. The valve **515B** may be opened during ground processing in order to provide coolant to the flow path **503B**. The gas line **506B** may include a valve **516B**. The valve **516B** may include an electronic valve. The valve **516B** may include a normally closed valve.

The flow path **503B** may include an accumulator **508B**. The accumulator **508B** may be configured to store coolant at a desired pressure. The flow path **503B** may include a regulator **509B** configured to regulate the pressure of the coolant in the accumulator **508B** and/or the flow path **503B**. The regulator **509B** may be set at a pressure of about 5 psia, about 10 psia, about 15 psia, about 20 psia, about 30 psia, about 40 psia, about 45 psia, and/or any value between the aforementioned values.

The flow path **503B** may include a valve **518B** between the accumulator **508B** and the plurality of release mechanisms **502B**. The valve **518B** may include an electronic valve. The valve **518B** may include a normally closed valve. During reentry of a rocket (e.g., the second stage **100**) through the atmosphere, the valve **518B** may be opened. As described above, channels in the release device **502B** are open to the atmosphere and/or plasma around the rocket during reentry through the atmosphere. A pressure of the atmosphere and/or plasma around the rocket may be less than the pressure of the coolant in the accumulator **508B** and/or the flow path **503B**. When the valve **518B** is opened, the difference in pressure may draw the coolant through the plurality of release mechanisms **502B** to cool the release mechanisms **502B**.

Each of the release mechanisms **502B** may include a metering valve **507B** and a one-way valve **510B**. The metering valve **507B** may be configured to restrict or control the flow rate of coolant into the corresponding release mechanism **502B** to ensure that coolant is distributed evenly to each release mechanisms **502B**. The metering valve **507B** may prevent or inhibit too much coolant from flowing the release mechanism **502B**. The one-way valve **510B** may be configured to prevent pressure buildup in the release mechanism **502B** generated when the coolant boils and phase changes to vapor from reversing a direction of flow of the coolant in the flow path **503B**.

Various modifications to the implementations described in this disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other implementations without departing from the spirit or scope of this disclosure. Thus, the disclosure is not intended to be limited to the implementations shown herein but is to be accorded the widest scope consistent with the claims, the principles and the novel features disclosed herein. The word “example” is used exclusively herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “example” is not necessarily to be construed as preferred or advantageous over other implementations, unless otherwise stated.

Certain features that are described in this specification in the context of separate implementations also may be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation also may be implemented in multiple implementations separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination may in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

21

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results, unless described as such. Additionally, other implementations are within the scope of the following claims. In some cases, the actions recited in the claims may be performed in a different order and still achieve desirable results.

It will be understood by those within the art that, in general, terms used herein are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to embodiments containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

What is claimed is:

1. A release device for a separation system of a rocket, the release device comprising:
a tubular body extending along a longitudinal axis from a proximal end to a distal end and defining a channel extending axially therethrough; and

22

a bolt comprising an axially extending shaft configured to be positioned within the channel of the tubular body and a transversely elongated head on a distal end of the shaft, wherein the bolt is configured to rotate about the longitudinal axis from a first position where the head is configured to engage an expendable component and a second position where the head is configured to disengage from the expendable component to thereby allow the bolt to translate proximally through the channel and allow the expendable component to separate from the rocket, and wherein a cooling channel extends through the bolt configured to flow coolant therethrough.

2. The release device of claim 1 further comprising a transverse actuation arm configured to rotate the shaft.

3. The release device of claim 1 further comprising a biasing element configured to bias the bolt proximally.

4. The release device of claim 1, wherein the head is configured to engage a seat of the expendable component, the seat defining a transversely elongated slot.

5. The release device of claim 1, wherein a proximal surface of the head is helical.

6. The release device of claim 1, wherein the release device comprises cooling channels extending through the body configured to flow coolant therethrough.

7. The release device of claim 1, wherein the cooling channel extending through the bolt extends to a distal opening at a distal end of the bolt.

8. The release device of claim 1, wherein the expendable component comprises an adaptor or a load spreader.

9. A release device for an expendable component of a rocket, the release device comprising:

a body comprising a channel extending through the body from a proximal end to a distal end;

a bolt comprising a shaft and a head on a distal end of the shaft; and

a cooling system configured to flow coolant to the body and through the bolt during reentry of the rocket into an atmosphere so that the release device is reusable.

10. The release device of claim 9, wherein the bolt is configured to heat up to cause the coolant to boil to prevent a temperature of the bolt from raising above a melting or annealing temperature of the bolt.

11. The release device of claim 9, wherein the cooling system comprises a recess in the head of the bolt, wherein the recess is configured to hold the coolant that boils to cool the head of the bolt during reentry of the rocket through the atmosphere.

12. The release device of claim 11, wherein the bolt comprises a cap coupled to a distal surface of the bolt, wherein the cap comprises a plurality of channels, and wherein the coolant is configured to boil in the plurality of channels to vent vapor out of the recess in the head and to the atmosphere.

13. The release device of claim 12, wherein the cap comprises a material with a high thermal diffusivity.

14. The release device of claim 13, wherein the bolt comprises titanium or the body comprises aluminum.

15. The release device of claim 11, wherein the body comprises an end cap and the cooling system comprises an annular channel in the end cap.

16. A method of operating a release device with a component for securement with a rocket, the method comprising:
positioning the component at a distal end of the release device;

distally translating a bolt of the release device into a recess of the component, the bolt comprising a cooling channel extending therethrough; and

rotating the bolt from a second position to a first position to engage a head of the bolt with the component. 5

17. The method of claim **16** further comprising rotationally biasing the bolt towards the first position.

18. The method of claim **16** further comprising proximally biasing the bolt.

19. The method of claim **16** further comprising rotating 10 the bolt from the first position to the second position to disengage the bolt from the component and proximally translating the bolt out of the recess of the component to retract the bolt into a body of the release device.

20. The method of claim **19** further comprising cooling 15 the bolt during reentry of the rocket through an atmosphere.

* * * * *